EFI[™] Fiery® eXpress 4.6





	FEATURES	Fiery eXpress 4.6
	Desktop application	•
	Cross-platform - Mac OS X and Microsoft® Windows®	•
FOUNDATIONS	Intuitive user interface	•
	100% focus on industry standards	•
	Continuous tone output	•
	Single workflow / print queue	•
[[]	Pre-defined linearization & profile sets	•
	Manual or fully automated job management	•
	Comprehensive job management tools (job list, preview)	•
	Wizard based licensing, setup and configuration	•
	Workflow templates for Proofing, Photo & Production	•
	Save/load workflow environments	•
	Preset saving	•
JSE	"Everyday" work mode (hides advanced settings)	•
EASE OF USE	Flexible job ticket configuration	•
E	Intuitive one-click spot color handling	•
EAS	Online updater	•
	Backup and restore	•
		incl. restore in Fiery XF
	Change of language in application	•
	RIP setup out of application via Unidriver	•
	ICC color management	•
	Multi-color profile support (up to 7 channels)	•
က	Device link profile support	•
TECHNOLOGIES AND STANDARDS	Adobe PostScript 3 Engine (CPSI)	3019
2	Multiple CPSI support	•
TA	Adobe PDF Print Engine (APPE) 2.5	•
0	Multi-processor support	•
A	Spot color libraries DIC, HKS®, PANTONE®,	
IES	PANTONE® Plus and Toyo	·
O,	ISO 12647-8 compliant validation printing	•
Q	ISO 12647-7 compliant contract proofing	•
上	G7 / SWOP / GRACoL compliant proofing	•
TEC	Ugra/Fogra media wedges v2.2 and v3.0	•
ED.	Idealliance ISO 12647-7 2009 and 2013 control strips	•
	Japan Color control strip	•
GR	Support of latest ISO profiles and characterization data	•
INTEGRAT	PDF/X-1, PDF/X-1a, PDF/X-3 support	•
AI I	Processing and printing of remote jobs	•
	Unicode support	•
	EXIF support	•

^{• =} Included • = New or enhanced in latest version



	0.1 11 1 10 10 10 10 10 10 10 10 10 10 10	
	Color adjustments (CMYK, RGB / Brightness, Contrast,	•
	Saturation, Blur / Sharpen, Dynamic Rendering Intent)	
Z -	Image interpolation (scaling)	•
DL	Gray conversion of colored files	•
¥	Spot color matching (of pre-defined libraries / custom spot colors)	•
T L	Object oriented color management	•
Image: Control of the	Visual correction on output data (ink channels)	•
COLOR HANDLING	RGB profile connector tool	•
	Processing of RGB PS/EPS/PDF based file formats in RGB color space	•
	Monitor profile selection - softproof capabilities	•
	Advanced speed settings	•
	Process resolution control (to speed up printing)	•
	Simultaneous job processing on multi-processor PCs for non PDF and	
_	PS formats	•
F	Rip and print on-the-fly	•
PRODUCTIVITY	Bi-directional printing (if supported by printer)	•
N N	Quicker processing of ImageEPS and ImagePDF	•
l i	Integrated Proof certification and label print	•
늅	Job-based optimization	•
	Support for EFI ES-1000, EFI ES-2000, X-Rite i1Pro, X-Rite i1Pro 2,	
	Epson SpectroProofer ILS20, Canon	•
	Spectrophotometer and HP Designjet Z Embedded	
	Nesting automatic or manual	•
Z	Contact sheet	•
110	Layout templates for single and multiple images	•
S	Uniform page scaling	•
PRODUCTION	Rotating, scaling, mirroring, aligning	•
PR	Cropping	•
	Cropping of PDF according to selected PDF box	•
	From Mac/Windows® via Hot folder, Virtual Printer, AppleTalk printer	•
R₹	From Mac/Windows® via Unidriver	•
ENTRY	Drag-and-drop	•
BE	Manual import	•
30B		
(0	PS, EPS, DCS1, DCS2, PDF	•
MATS	PSD, TIFF, JPEG, JPEG2000, image PDF, image EPS	•
R.	RAW	•
PO	RPF (Remote Proofing Format)	•
FILE FOR		
臣		
	Support of inkjet, laser and LED printers	•
Ŀ	RGB driver support	•
J.J.	TIFF CMYK export accord. ISO printing condition	•
OUTPUT	Printing via network (TCP/IP, Bonjour), USB or system printer	•
	(Windows [®] only)	
	Borderless printing for printer supporting this feature	•



^{• =} Included • = New or enhanced in latest version



	Agfa	•
	Canon	•
S	Encad [®]	•
臣	EPSON [®]	•
SUPORTERD PRINTERS	HP [®]	•
Ы	Kodak	•
ERI	Mimaki [®]	•
L TX	Mutoh	•
) F	OKI®	•
รร	Roland [®]	•
	Seiko	•
	Xerox [®]	•
LANGUAGES	English, French, Italian, German, Polish, Spanish, Japanese, Simplified Chinese	•

PRODUCT SIZES		
	Fiery eXpress Small	Supports all printers up to and including 18" / A2
	Fiery eXpress Large	Supports 24" printers and larger

RECOMMENDED SYSTEM REQUIREMENTS	
Operating Systems	Microsoft® Windows® 7, 8, 8.1, 10 (new) Mac OS X 10.9, 10.10, 10.11 (new), 10.12 (new)
Hardware Requirements – Windows®	Windows® 2 GHz Pentium IV PC, 2 GB Ram, 4 GB recommended 10/100 Mbit Network 1 available USB port
Hardware Requirements – Macintosh	Macintosh with Intel CPU, 2 GB Ram, 4 GB recommended 10/100 Mbit Network, 1 available USB port

Note: Fiery eXpress is a 32-bit software. It runs on 64-bit systems in 32-bit mode.

Color Managemet Partner Sommerstr. 7 90762 Fürth Tel 0911-97798271 Email info@cm-partner.de

• = Included • = New or enhanced in latest version

